

Examples of patents indexed in different categories:

LINK	COUNTRY	PATENT NUMBER	PUBLICATION DATE Day-Month-Year	APPLICANT	PRIORITY	Priority date D-M-Y	PRIORITY NUMBER	EQUIVALENTS	TITLE	KEY WORDS
P159	WO	02029735	11/04/2002	CUMMINS ALLISON	US	05/10/2000	US290009958163	AU194362A5 CA24824663AA EP1232139A2 WO0229735A2 WO0229735A3	METHOD AND APPARATUS FOR DOCUMENT IDENTIFICATION AND AUTHENTICATION	Magnetic sensor
Bk285	US	2002109830	15/08/2002	LIU DONALD PAKMAN	US	09/02/2001	US289490780691		CURRENCY VALIDATOR	UV light
P2264	EP	1057136	01/10/2003	CASHCODE	CA	25/02/1998	CA1998002238523	AU7535507 AU7146099A1 CA2239523A CA17831721 DE69511745C8 JP2258548772 US6457643 WO994416A1	INDUCTION SENSOR	
P354	EP	1179810	13/02/2002	EUROP CENTRAL BANK	EP	11/08/2000			SECURITY DOCUMENTS DATA EXCHANGE SYSTEM	
P1864	WO	03032243	17/04/2003	GIESECKE & DEVRIENT	DE	05/10/2001	DE20011049265	DE10149265	SECURITY MARKING FOR GOODS OR PACKAGES, USED IN AUTHENTICATION OR LOGISTICS TRACKING, COMPRISES OVERPRINTING WITH INKS HAVING DIFFERENT SPECTRAL PROPERTIES	IR printing overprinting
P1554	JP	11005385	12/01/1999	TOPPAN PRINTING					LOTTERY TICKET TAKING PREVENTIVE MEASURE AGAINST FORGERY	Shielding layer Fluorescent Infrared
P1532	WO	02101147	19/12/2002	REXOR					SECURITY THREAD OR TRANSFER FILM FOR HOT PROCESS MARKING OF BANK NOTES, DOCUMENTS OR OTHER ARTICLES TO BE MADE SECURE	Laser letters opaque layer
P670	US	5935696	10/08/1999	MOBIL OIL CORP					MULTILAYER FILM STRUCTURES FOR USE IN THE PRODUCTION OF BANKNOTES OR THE LIKE	
P2313	WO	03095188	20/11/2003	DE LA RUE					A METHOD OF MANUFACTURING A FIBROUS SUBSTRATE INCORPORATING AN ELONGATE IMPERMEABLE SECURITY ELEMENT	Window
TH252	WO	03055683	23/05/2003	ARJO WIGGINS					METHOD FOR MAKING AN ARTICLE COMPRISING A SHEET AND AT LEAST AN ELEMENT DIRECTLY MOUNTED THEREON	Integrated circuit cavity
P1249	JP	2002226740	14/08/2002	TOPPAN PRINTING					INK JET INK COMPOSITION, INK JET INK, FORGERY- PREVENTING IMAGE-FORMING BODY, MANUFACTURING METHOD OF FORGERY- PREVENTING IMAGE-FORMING	

Full text patent

English abstract

JP2002226740

INK JET INK COMPOSITION, INK JET INK, FORMING BODY, AND DISCRIMINATING M

Publication date: 2002-08-14
 Inventor(s): KIJIMA ATSUSHI ; HORIE KIYOSHI ; MA
 Applicant(s): TOPPAN PRINTING CO LTD
 Requested Patent: JP2002226740
 Application Number: JP20010023278 20010131
 Priority Number(s):
 IPC Classification: C09D11/00; B41J2/01; B41M3/14;

Abstract

Topic: To provide an ink composition and an ink suitable for ink jet printing, which requires high security (representative examples thereof) and a discriminating manufacturing method thereof and a discriminating method thereof.

INVENTION: An ink jet ink comprising both a colorless dye and a fluorescent dye, an image-forming body. Thus, even if an image of the pigment near the outermost layer is removed, an image of the fluorescent dye having soaked into the substrate remains unremoved at the same place thereby permitting easy detection of a dishonest act.

(12) DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITÉ DE COOPÉRATION EN MATIÈRE DE BREVETS (PCT)

(19) Organisation Mondiale de la Propriété Intellectuelle
Bureau international

(43) Date de la publication internationale: 10 juillet 2003 (16.07.2003)

(40) Numéro de publication internationale: WO 03/055683 A1

(51) Classification internationale des brevets: B22B 31/08, B42D 15/06, D21H 21/00

(52) Date de dépôt international: 20 novembre 2002 (08.11.2002)

(53) Langue de dépôt: français

(54) Demandes relatives à la priorité: 02/10986 20 novembre 2002 (08.11.2002) FR

(55) Dépôté (pour une ou les États désignés) par (53) : ARJO WIGGINS SECURITY SAS (FR) 117, quai de Président Roosevelt, F-92482 Issy les Moulineaux Cedex (FR)

(56) Inventeur(s): DOUBILET, Pierre (FR)

(57) Mandataire : CABRE, Claudine, Arjo Wiggins, 117, quai de Président Roosevelt, F-92482 Issy les Moulineaux Cedex (FR)

(58) États désignés (autres que) : AU, AT, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GR, GT, GU, HK, HN, HU, IL, IN, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PK, PL, PT, RU, RW, SA, SG, SI, SK, SL, SM, SN, SV, TH, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

Désignation en vertu de la règle 4.17: relative au droit de déposer de revendiquer la priorité de la demande antérieure (règle 4.17(a)) pour les désignations suivantes: AE, AG, AI, AM, AR, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GR, GT, GU, HK, HN, HU, IL, IN, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PK, PL, PT, RU, RW, SA, SG, SI, SK, SL, SM, SN, SV, TH, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW. Brevets européens (AM, AR, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GR, GT, GU, HK, HN, HU, IL, IN, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PK, PL, PT, RU, RW, SA, SG, SI, SK, SL, SM, SN, SV, TH, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW).

(54) Titre: METHOD FOR MAKING AN ARTICLE COMPRISING A SHEET AND AT LEAST AN ELEMENT DIRECTLY MOUNTED THEREON

(55) Titre: PROCÉDE DE FABRICATION D'UN ARTICLE COMPORTANT UNE FEUILLE ET AU MOINS UN ÉLÉMENT RAPPORTÉ SUR CETTE FEUILLE

(57) Abstract: The invention concerns a method for making an article (1) comprising a sheet (2) and at least an element (3) having a certain thickness, comprising the following steps: providing a sheet (2) with at least a cavity (3) emerging on one side; placing in said cavity (3) said element by pressing on said side a structure (5) comprising at least a layer bearing the element, said structure being positioned relative to the sheet (2) so that the element (4) is urged to be housed at least partly in said cavity (3).

(57) Abstrégé : La présente invention concerne un procédé de fabrication d'un article (1) comportant une feuille (2) et au moins un élément (3) ayant une certaine épaisseur, comprenant les étapes suivantes: fournir une feuille (2) avec au moins une cavité (3) débouchant sur une face; placer dans cette cavité (3) ledit élément en appuyant sur ladite face une structure (5) comportant au moins une couche portant l'élément, ladite structure étant positionnée par rapport à la feuille (2) de manière à ce que l'élément (4) vienne se loger au moins partiellement dans la cavité (3).

TURING METHOD OF FORGERY- PREVENTING IMAGE-

gery, falsification, alteration and the like of an image-forming body which acts as if they are done, and the like, and to provide an image-forming body, a

ial impregnated with the ink is employed as a substrate of the image-forming body. Thus, even if an image of the pigment near the outermost layer is removed, an image of the fluorescent dye having soaked into the substrate remains unremoved at the same place thereby permitting easy detection of a dishonest act.

